



- a strong solution for the environment



MIXER

The purpose of the ReTec mixer is to mix different materials. For example, it is ideal for mixing horse feed, animal feed and other types of agricultural feed. If sludge is to be mixed with lime to obtain a good end product for spreading in the field, this task can also be done with ease.

The application possibilities are many, and the construction can be designed to suit your specific task.

The mixer is made so that the material is filled in the bottom of the machine, after which it is led to the top of the 2 screws. Due to gravity, the material will continuously be carried down to the lower part of the machine and the mixing will then start all over again. Dosing of the finished mix is done by opening the door under the top of the mixer

Technical data	
Dimensions	H x W x L: 4229 x 2917 x 5850 mm
Capacity	16-20 m ³ /h (standard mixer)
Content	Approx. 20 m ³
Transmission	2 x Nordgear, 15 kW engine, 400 V 50 Hz. The transmission is situated in the top end of the mixer.
Auger winding	Ø 460 mm, 15 mm thickness. Augerwinding and shafts in black steel
Options	RAL colour. Stainless steel AISI 304. Weighing cells.



ReTec Miljø ApS
Fjordagervej 38
DK-6100 Haderslev

Tel.: +45 7456 8106
Fax: +45 7456 8581
VAT: DK 25 86 24 22

sales@retec.dk
www.retec.dk

ReTec develops, constructs and manufactures special machines for the waste and recycling industry. We offer practical solutions to our customer's needs, helping them increase profitability in their business.